



Canadian Wholesale Lighting
5-1525 Dilworth Dr Kelowna BC V1Y9N5
Ph. 778 484 (CWLL) 2955 Web. www.cwll.ca

TRIPROOF AND INTEGRATED LIGHTING

- Warehouses
- Supermarkets
- Packing
- Carwash
- Schools
- Industrial
- Commercial Space



Features:

1. No flicker, the light output is even & beautiful
2. Big beam angle: 300°
3. Seamless connection
4. Switch function is available.
5. Lifespan: 40000hrs
6. 3 years warranty
7. Certification: ETL, FCC, DLC, Prop65



Physical Characteristics	
Size	1200mm
LED	92*HL2835
Socket Type	G5
Lampshade	PC Frosted
Effective Lifetime	40000Hrs
Qualification	ETL FCC DLC Prop65
Storage Humidity	<90%
Electrical Characteristics	
Input Voltage	AC120-277V
Lamp Wattage	18W
Power Factor	0.95
Frequency	50/60Hz
Photometric Characteristics	
Lumen Output	1980lm/2610lm
Energy rating	A
Color Temperature	4000k
Beam Angle	300°
Color Rendering Index	Ra80
Operating Temperature	-20°C ~ +40°C
Specification	
Length L	1200mm

Canadian Wholesale Lighting

5-1525 Dilworth Dr Kelowna BC V1Y9N5
Ph. 778 484 (CWLL) 2955 Web. www.cwll.ca



LED Tri-Proof light is incredibly durable and has earned a high IP66 rating which means it can withstand dust, water, high pressure and corrosive substances.

With an IP66 rating this light is perfect for use on ceilings in Car Parks, Warehouses, Offices, Supermarkets, outdoor areas and school science laboratories.

Canadian Wholesale Lighting

5-1525 Dilworth Dr Kelowna BC V1Y9N5

Ph. 778 484 (CWLL) 2955 Web. www.cwll.ca

This fixture has the same light output as a fluorescent tube twice its size whilst using much less energy, this is due to the highly efficient LED chips used. This fitting is easy to install by simply attaching it to the brackets provided and wiring it directly to the mains, this saves you money in installation costs as well as running costs.

* PC diffuser + Aluminum body

*Input voltage: 90-305VAC, 277-528VAC, DC12V/24V.

*IP66, waterproof + dustproof+ Moisture-proof + Anti corrosion.

*Available in 0~10 V / Triac / DALI dimming, emergency, motion sensor.

*High energy efficiency of 130 lumens/Watt means you get more light with less energy use.

*50,000-hour average operating life significantly reduces the frequency of lamp replacements.

*Support wiring from side, back, play-and-plug, or cable self-mounted.

*Support ceiling, wall mounted, suspended installation.

*Vapor tight/tri-proof enclosure protects against dust, water jets, and corrosion.

*5-year warranty.

*Common applications: workshops, car wash bays, parking garages, corridors, breweries, laundries, refrigerated storage, industrial kitchens, grain silos, barns, and an enormous number of other industrial, commercial, farming, and manufacturing applications.

*Certification: ETL cETL

*LED modules comply with IESNA LM-79 and LM-80 standards. DesignLights Consortium™ Qualified and classified for DLC Standard (some models are not DLC qualified), refer to www.designlights.org for details.